## **AMENDMENTS TO THE CLAIMS**

The claims in this listing will replace all prior versions, and listings, of claims in the application.

## Listing of Claims:

- 1. (Currently Amended) Method for producing a fiber-composite material for producing fiber-composite components, the fiber-composite material comprising reinforcement fibers, resin and a filler, characterized in that the filler comprises comprising at least one of ground and/or and cut reinforcement fibers.
- 2. (Currently Amended) Method according to claim 1, characterized in that the wherein the filler comprises ground fibers having a particle size of the ground filler is less than 2 mm.
- 3. (Currently Amended) Method according to claim 1, characterized in that the wherein the filler comprises cut fibers having a size of the cut fibers is less than 20 mm.
- 4. (Currently Amended) Method according to claim 1, characterized in that wherein the at least one of ground material and/or the and cut reinforcement fibers is mixed with the resin that forms the <u>a</u> subsequent matrix of the fiber-composite component.
- 5. (Currently Amended) Method according to claim [[1]] 4, characterized in that wherein the resin filler mixture is processed into a film.
- 6. (Currently Amended) Method according to claim 5, characterized in that wherein the resin filler film is applied to <u>a</u> semi-finished textile <u>product</u> products, e.g., woven fabrics, braided fabrics, knitted fabrics, unidirectional or multiaxial laid fabrics.
- 7. (Currently Amended) Method according to claim [[1]] 6, characterized in that wherein the resin filler film is introduced as such into a component mold before the actual semi-finished textile product is placed in the component mold, e.g., as a preform.

## 00039342.DOC

- 8. (Currently Amended) Method according to claim 1, characterized in that wherein the resin filler mixture fiber-composite material is applied into a component mold or onto a semi-finished textile product in a spray method.
- 9. (Currently Amended) Method according to claim [[1]] <u>8</u>, characterized in that wherein the semi-finished textile products product sprayed with the resin filler mixture are material is also used for producing preforms.
  - 10. (Canceled)
- 11. (New) Method according to claim 6, wherein the semi-finished textile product comprises woven fabrics, braided fabrics, knitted fabrics, unidirectional fabrics or multiaxial laid fabrics.
- 12. (New) Method according to claim 7, wherein the resin filler film comprises a preform.